

**अनिवार्य आवश्यकताएँ**

**संख्या : TEC58432108**

**Essential Requirements**

**ER No. : TEC58432108**

---

---

**VHF UHF Radio System Equipment**

© टीईसी, २०२१  
© TEC, 2021

---

---

MTCTE के तहत जारी:

Issued under MTCTE by:

**दूरसंचार अभियांत्रिकी केंद्र**

**भारत सरकार**

**खुर्शीद लाल भवन, जनपथ, नई दिल्ली - 110001, भारत**

**Telecommunication Engineering Centre**

**Government of India**

**Khurshid Lal Bhawan, Janpath, New Delhi-110001, INDIA**

---

Essential Requirements for:

## VHF UHF Radio System Equipment

Certification Scheme: **GCS**

Product Fee Group: **C**

This ER covers VHF and UHF Radio Base Station and User Terminals

*Note: Annexures referred to in this ER are Annexures as mentioned in "Annexures to ERs" No. TEC/SD/DD/TCP-222/02/June19 as updated from time to time and available on MTCTE portal.*

This product has the following variants:

1. VHF UHF Base Station - Baseband plus Radio
2. VHF UHF Base Station - Radio Only
3. VHF UHF Baseband Equipment without Radio
4. VHF UHF Fixed Station
5. VHF UHF Handheld Portable Stations
6. VHF UHF Mobile Stations

### 1. Variant 1 : VHF UHF Base Station - Baseband plus Radio

#### 1.1 Parameters Linked with Product Variant

S.No.	Parameter Name	Standard Name
1.1.1	Conducted And Radiated Emission - Class A	TEC EMI EMC Standard CISPR 22/32 EN55022/32. Annex-B
1.1.2	Conformance to standards for VHF or UHF Radio Systems	ETSI EN 300xxx 301-xxx. Annex-C3
1.1.3	Frequency for VHF or UHF equipments	NFAP. Annex-C1

1.1.4	Immunity to AC Voltage Dips and Short Interruptions	TEC EMI EMC Standard EN/IEC:61000-4-11. Annex-B
1.1.5	Immunity to DC Voltage Dips and Short Interruptions	EN/IEC:61000-4-29. Annex-B
1.1.6	Immunity to Electrostatic Discharge	TEC EMI EMC Standard EN/IEC:61000-4-2. Annex-B
1.1.7	Immunity to Fast Transients (Burst)	TEC EMI EMC Standard EN/IEC:61000-4-4. Annex-B
1.1.8	Immunity to Radiated RF	TEC EMI EMC Standard EN/IEC:61000-4-3. Annex-B
1.1.9	Immunity to RF Field Induced Conducted Disturbance	TEC EMI EMC Standard EN/IEC:61000-4-6. Annex-B
1.1.10	Immunity to Surges	TEC EMI EMC Standard EN/IEC:61000-4-5. Annex-B
1.1.11	IT Equipment Safety	IS 13252-1 or IEC:60950-1 or IEC 62368-1. Annex-A1
1.1.12	IT Equipment Safety for Radio Products	EN/IEC 60215:2016. Annex-A3
1.1.13	Max Transmit Power for VHF or UHF Base Stn	As per DoT/WPC license conditions. Annex-C2

## 1.2 Interface 1 : 1 G Optical Ethernet

S.No.	Parameter Name	Standard Name
1.2.1	Average Launch power for 1 GE Opt	IEEE 802.3z Cl. 38. Annex-H
1.2.2	Receiver Sensitivity 1 GE Opt	IEEE 802.3z Cl. 38. Annex-H
1.2.3	Wavelength for 1 GE Opt	IEEE 802.3z Cl. 38. Annex-H

## 1.3 Interface 2 : 10 G Optical Ethernet

S.No.	Parameter Name	Standard Name
1.3.1	Average Launch power for 10 GE Opt	IEEE 802.3ae Cl. 52. Annex-H
1.3.2	Receiver Sensitivity 10 GE Opt	IEEE 802.3ae Cl. 52. Annex-H
1.3.3	Wavelength for 10 GE Opt	IEEE 802.3ae Cl. 52. Annex-H

## 1.4 Interface 3 : 100 G Optical Ethernet

S.No.	Parameter Name	Standard Name
-------	----------------	---------------

1.4.1	Average Launch power for 100 GE Opt	IEEE 802.3ba Cl. 86 88. Annex-H
1.4.2	Receiver Sensitivity 100 GE Opt	IEEE 802.3ba Cl. 86 88. Annex-H
1.4.3	Wavelength for 100 GE Opt	IEEE 802.3ba Cl. 86 88. Annex-H

#### 1.5 Interface 4 : 2 Mbps - E1

S.No.	Parameter Name	Standard Name
1.5.1	Input Jitter Tolerance for 2 Mbps Int	ITU-T G.823 / ETSI TBR-4. Annex-I
1.5.2	Input Return Loss for 2 Mbps Int	ITU-T G.703 / ETSI TBR-4 Cl. 9.3.1. Annex-I
1.5.3	Nominal Bit Rate with Tolerance for 2 Mbps Int	ITU-T G.703 / ETSI TBR-4 Cl. 9.2.3. Annex-I
1.5.4	Output Jitter for 2 Mbps Int	ITU-T G.823 / ETSI TBR-4. Annex-I
1.5.5	Pulse Mask for 2 Mbps Int	ITU-T G.703 / ETSI TBR-4 Cl. 9.2.1. Annex-I

#### 1.6 Interface 5 : 40 G Optical Ethernet

S.No.	Parameter Name	Standard Name
1.6.1	Average Launch power for 40 GE Opt	IEEE 802.3ba Cl. 86 87. Annex-H
1.6.2	Receiver Sensitivity 40 GE Opt	IEEE 802.3ba Cl. 86 87. Annex-H
1.6.3	Wavelength for 40 GE Opt	IEEE 802.3ba Cl. 86 87. Annex-H

#### 1.7 Interface 6 : Bluetooth Low Energy

S.No.	Parameter Name	Standard Name
1.7.1	EIRP for BLE Interface	WPC GSR 45(E). Annex-G4 (4.2)
1.7.2	Frequency of Operation for BLE Interface	Latest NFAP. Annex-G4(4.1)
1.7.3	Spurious Emission for BLE Interface	Annex G3

#### 1.8 Interface 7 : Fast Ethernet Electrical

S.No.	Parameter Name	Standard Name
1.8.1	Link Speed and Autonegotiation Test FE	IEEE 802.3 Annex-H

#### 1.9 Interface 8 : Gigabit Ethernet Electrical

S.No.	Parameter Name	Standard Name
1.9.1	Link Speed and Autonegotiation Test GE	IEEE 802.3. Annex-H

### 1.10 Interface 9 : Near Field Communication

S.No.	Parameter Name	Standard Name
1.10.1	Frequency of Operation for NFC Int	Latest NFAP. Annex-G6(6.1)
1.10.2	Spurious Emission for NFC Int	Annex- G3

### 1.11 Interface 10 : STM-1 Electrical

S.No.	Parameter Name	Standard Name
1.11.1	Input Jitter Tolerance STM-1 Electrical	ITU-T G.825. Annex-K
1.11.2	Input Return Loss for STM-1 Electrical	ITU-T G.703. Annex-K
1.11.3	Nominal Bit Rate with Tolerance STM-1 Electrical Int	ITU-T G.703. Annex-K
1.11.4	Output Jitter for STM-1 Electrical Int	ITU-T G.825. Annex-K
1.11.5	Pulse Mask for STM-1 Electrical Int	ITU-T G.703. Annex-K

### 1.12 Interface 11 : STM-1 Optical

S.No.	Parameter Name	Standard Name
1.12.1	Input Jitter Tolerance for STM-1 Opt	ITU-T G.825. Annex-K
1.12.2	Mean Launched Power for STM-1 Opt Int	ITU-T G.957. Annex-K
1.12.3	Nominal Bit Rate with Tolerance STM-1 Opt Int	ITU-T G.957. Annex-K
1.12.4	Operating Wavelength Range for STM-1 Opt Int	ITU-T G.957. Annex-K
1.12.5	Output Jitter for STM-1 Opt Int	ITU-T G.783 G.825 Annex-K
1.12.6	Receiver Overload for STM-1 Opt Int	ITU-T G.957. Annex-K
1.12.7	Receiver Sensitivity for STM-1 Opt Int	ITU-T G.957. Annex-K

### 1.13 Interface 12 : STM-16 Optical

S.No.	Parameter Name	Standard Name
1.13.1	Input Jitter Tolerance for STM-16 Opt	G.825. Annex-K
1.13.2	Mean Launched Power for STM-16 Opt Int	ITU-T G.957. Annex-K
1.13.3	Nominal Bit Rate with Tolerance STM-16 Opt Int	ITU-T G.957. Annex-K

1.13.4	Operating Wavelength Range for STM-16 Opt Int	ITU-T G.957. Annex-K
1.13.5	Output Jitter for STM-16 Opt Int	ITU-T G.783. Annex-K
1.13.6	Receiver Overload for STM-16 Opt Int	ITU-T G.957. Annex-K
1.13.7	Receiver Sensitivity for STM-16 Opt Int	ITU-T G.957. Annex-K

#### 1.14 Interface 13 : STM-4 Optical

S.No.	Parameter Name	Standard Name
1.14.1	Input Jitter Tolerance for STM-4 Opt	ITU-T G.825. Annex-K
1.14.2	Mean Launched Power for STM-4 Opt Int	ITU-T G.957. Annex-K
1.14.3	Nominal Bit Rate with Tolerance STM-4 Opt Int	ITU-T G.957 Annex-K
1.14.4	Operating Wavelength Range for STM-4 Opt Int	ITU-T G.957. Annex-K
1.14.5	Output Jitter for STM-4 Opt Int	ITU-T G.783. Annex-K
1.14.6	Receiver Overload for STM-4 Opt Int	ITU-T G.957. Annex-K
1.14.7	Receiver Sensitivity for STM-4 Opt Int	ITU-T G.957. Annex-K

#### 1.15 Interface 14 : STM-64 Optical

S.No.	Parameter Name	Standard Name
1.15.1	Input Jitter Tolerance for STM-64 Opt	ITU-T G.825. Annex-K
1.15.2	Mean Launched Power for STM-64 Opt Int	ITU-T G.691. Annex-K
1.15.3	Nominal Bit Rate with Tolerance STM-64 Opt Int	ITU-T G.707 Annex-K
1.15.4	Operating Wavelength Range for STM-64 Opt Int	ITU-T G.691. Annex-K
1.15.5	Output Jitter for STM-64 Opt Int	ITU-T G.783. Annex-K
1.15.6	Receiver Overload for STM-64 Opt Int	ITU-T G.691. Annex-K
1.15.7	Receiver Sensitivity for STM-64 Opt Int	ITU-T G.691. Annex-K

#### 1.16 Interface 15 : WiFi

S.No.	Parameter Name	Standard Name
1.16.1	2.4 GHz WiFi Radio Conformance	ETSI EN 300 328 or FCC CFR47 pt 15.247

		or FCC CFR47 pt 15.249. Annex-G3
1.16.2	5 GHz WiFi Radio Conformance	ETSI EN 301 893 or FCC CFR47 pt 15.407 or FCC CFR47 pt 15.249. Annex-G3
1.16.3	EIRP for Wifi Interface	Latest NFAP and GSRs issued by DoT WPC. Annex-G2
1.16.4	Frequency for WiFi equipments	DoT WPC GSR No. 45(E) 1048(E). Annex-G1

## 2. Variant 2 : VHF UHF Base Station - Radio Only

### 2.101 Parameters Linked with Product Variant

S.No.	Parameter Name	Standard Name
2.1.1	Conducted And Radiated Emission - Class A	TEC EMI EMC Standard CISPR 22/32 EN55022/32. Annex-B
2.1.2	Conformance to standards for VHF or UHF Radio Systems	ETSI EN 300xxx 301-xxx. Annex-C3
2.1.3	Frequency for VHF or UHF equipments	NFAP. Annex-C1
2.1.4	Immunity to AC Voltage Dips and Short Interruptions	TEC EMI EMC Standard EN/IEC:61000-4-11. Annex-B
2.1.5	Immunity to DC Voltage Dips and Short Interruptions	EN/IEC:61000-4-29. Annex-B
2.1.6	Immunity to Electrostatic Discharge	TEC EMI EMC Standard EN/IEC:61000-4-2. Annex-B
2.1.7	Immunity to Fast Transients (Burst)	TEC EMI EMC Standard EN/IEC:61000-4-4. Annex-B
2.1.8	Immunity to Radiated RF	TEC EMI EMC Standard EN/IEC:61000-4-3. Annex-B
2.1.9	Immunity to RF Field Induced Conducted Disturbance	TEC EMI EMC Standard EN/IEC:61000-4-6. Annex-B
2.1.10	Immunity to Surges	TEC EMI EMC Standard EN/IEC:61000-4-5. Annex-B
2.1.11	IT Equipment Safety	IS 13252-1 or IEC:60950-1 or IEC 62368-1. Annex-A1
2.1.12	IT Equipment Safety for Radio Products	EN/IEC 60215:2016. Annex-A3
2.1.13	Max Transmit Power for VHF or UHF Base	As per DoT/WPC license conditions. Annex-

Stn	C2
-----	----

### 3. Variant 3 : VHF UHF Baseband Equipment without Radio

#### 3.1 Parameters Linked with Product Variant

S.No.	Parameter Name	Standard Name
3.1.1	Conducted And Radiated Emission - Class A	TEC EMI EMC Standard CISPR 22/32 EN55022/32. Annex-B
3.1.2	Immunity to AC Voltage Dips and Short Interruptions	TEC EMI EMC Standard EN/IEC:61000-4-11. Annex-B
3.1.3	Immunity to DC Voltage Dips and Short Interruptions	EN/IEC:61000-4-29. Annex-B
3.1.4	Immunity to Electrostatic Discharge	TEC EMI EMC Standard EN/IEC:61000-4-2. Annex-B
3.1.5	Immunity to Fast Transients (Burst)	TEC EMI EMC Standard EN/IEC:61000-4-4. Annex-B
3.1.6	Immunity to Radiated RF	TEC EMI EMC Standard EN/IEC:61000-4-3. Annex-B
3.1.7	Immunity to RF Field Induced Conducted Disturbance	TEC EMI EMC Standard EN/IEC:61000-4-6. Annex-B
3.1.8	Immunity to Surges	TEC EMI EMC Standard EN/IEC:61000-4-5. Annex-B
3.1.9	IT Equipment Safety	IS 13252-1 or IEC:60950-1 or IEC 62368-1. Annex-A1

#### 3.2 Interface 1 : 1 G Optical Ethernet

S.No.	Parameter Name	Standard Name
3.2.1	Average Launch power for 1 GE Opt	IEEE 802.3z Cl. 38. Annex-H
3.2.2	Receiver Sensitivity 1 GE Opt	IEEE 802.3z Cl. 38. Annex-H
3.2.3	Wavelength for 1 GE Opt	IEEE 802.3z Cl. 38. Annex-H

#### 3.3 Interface 2 : 10 G Optical Ethernet

S.No.	Parameter Name	Standard Name
3.3.1	Average Launch power for 10 GE Opt	IEEE 802.3ae Cl. 52. Annex-H



3.3.2	Receiver Sensitivity 10 GE Opt	IEEE 802.3ae Cl. 52. Annex-H
3.3.3	Wavelength for 10 GE Opt	IEEE 802.3ae Cl. 52. Annex-H

### 3.4 Interface 3 : 100 G Optical Ethernet

S.No.	Parameter Name	Standard Name
3.4.1	Average Launch power for 100 GE Opt	IEEE 802.3ba Cl. 86 88. Annex-H
3.4.2	Receiver Sensitivity 100 GE Opt	IEEE 802.3ba Cl. 86 88. Annex-H
3.4.3	Wavelength for 100 GE Opt	IEEE 802.3ba Cl. 86 88. Annex-H

### 3.5 Interface 4 : 2 Mbps - E1

S.No.	Parameter Name	Standard Name
3.5.1	Input Jitter Tolerance for 2 Mbps Int	ITU-T G.823 / ETSI TBR-4. Annex-I
3.5.2	Input Return Loss for 2 Mbps Int	ITU-T G.703 / ETSI TBR-4 Cl. 9.3.1. Annex-I
3.5.3	Nominal Bit Rate with Tolerance for 2 Mbps Int	ITU-T G.703 / ETSI TBR-4 Cl. 9.2.3. Annex-I
3.5.4	Output Jitter for 2 Mbps Int	ITU-T G.823 / ETSI TBR-4. Annex-I
3.5.5	Pulse Mask for 2 Mbps Int	ITU-T G.703 / ETSI TBR-4 Cl. 9.2.1. Annex-I

### 3.6 Interface 5 : 40 G Optical Ethernet

S.No.	Parameter Name	Standard Name
3.6.1	Average Launch power for 40 GE Opt	IEEE 802.3ba Cl. 86 87. Annex-H
3.6.2	Receiver Sensitivity 40 GE Opt	IEEE 802.3ba Cl. 86 87. Annex-H
3.6.3	Wavelength for 40 GE Opt	IEEE 802.3ba Cl. 86 87. Annex-H

### 3.7 Interface 6 : Bluetooth Low Energy

S.No.	Parameter Name	Standard Name
3.7.1	EIRP for BLE Interface	WPC GSR 45(E). Annex-G4 (4.2)
3.7.2	Frequency of Operation for BLE Interface	Latest NFAP. Annex-G4(4.1)
3.7.3	Spurious Emission for BLE Interface	Annex G3

### 3.8 Interface 7 : Fast Ethernet Electrical

S.No.	Parameter Name	Standard Name
-------	----------------	---------------

3.8.1	Link Speed and Autonegotiation Test FE	IEEE 802.3 Annex-H
-------	--	--------------------

### 3.9 Interface 8 : Gigabit Ethernet Electrical

S.No.	Parameter Name	Standard Name
3.9.1	Link Speed and Autonegotiation Test GE	IEEE 802.3. Annex-H

### 3.10 Interface 9 : Near Field Communication

S.No.	Parameter Name	Standard Name
3.10.1	Frequency of Operation for NFC Int	Latest NFAP. Annex-G6(6.1)
3.10.2	Spurious Emission for NFC Int	Annex- G3

### 3.11 Interface 10 : STM-1 Electrical

S.No.	Parameter Name	Standard Name
3.11.1	Input Jitter Tolerance STM-1 Electrical	ITU-T G.825. Annex-K
3.11.2	Input Return Loss for STM-1 Electrical	ITU-T G.703. Annex-K
3.11.3	Nominal Bit Rate with Tolerance STM-1 Electrical Int	ITU-T G.703. Annex-K
3.11.4	Output Jitter for STM-1 Electrical Int	ITU-T G.825. Annex-K
3.11.5	Pulse Mask for STM-1 Electrical Int	ITU-T G.703. Annex-K

### 3.12 Interface 11 : STM-1 Optical

S.No.	Parameter Name	Standard Name
3.12.1	Input Jitter Tolerance for STM-1 Opt	ITU-T G.825. Annex-K
3.12.2	Mean Launched Power for STM-1 Opt Int	ITU-T G.957. Annex-K
3.12.3	Nominal Bit Rate with Tolerance STM-1 Opt Int	ITU-T G.957. Annex-K
3.12.4	Operating Wavelength Range for STM-1 Opt Int	ITU-T G.957. Annex-K
3.12.5	Output Jitter for STM-1 Opt Int	ITU-T G.783 G.825 Annex-K
3.12.6	Receiver Overload for STM-1 Opt Int	ITU-T G.957. Annex-K
3.12.7	Receiver Sensitivity for STM-1 Opt Int	ITU-T G.957. Annex-K

### 3.13 Interface 12 : STM-16 Optical

S.No.	Parameter Name	Standard Name
3.13.1	Input Jitter Tolerance for STM-16 Opt	G.825. Annex-K
3.13.2	Mean Launched Power for STM-16 Opt Int	ITU-T G.957. Annex-K
3.13.3	Nominal Bit Rate with Tolerance STM-16 Opt Int	ITU-T G.957. Annex-K
3.13.4	Operating Wavelength Range for STM-16 Opt Int	ITU-T G.957. Annex-K
3.13.5	Output Jitter for STM-16 Opt Int	ITU-T G.783. Annex-K
3.13.6	Receiver Overload for STM-16 Opt Int	ITU-T G.957. Annex-K
3.13.7	Receiver Sensitivity for STM-16 Opt Int	ITU-T G.957. Annex-K

### 3.14 Interface 13 : STM-4 Optical

S.No.	Parameter Name	Standard Name
3.14.1	Input Jitter Tolerance for STM-4 Opt	ITU-T G.825. Annex-K
3.14.2	Mean Launched Power for STM-4 Opt Int	ITU-T G.957. Annex-K
3.14.3	Nominal Bit Rate with Tolerance STM-4 Opt Int	ITU-T G.957 Annex-K
3.14.4	Operating Wavelength Range for STM-4 Opt Int	ITU-T G.957. Annex-K
3.14.5	Output Jitter for STM-4 Opt Int	ITU-T G.783. Annex-K
3.14.6	Receiver Overload for STM-4 Opt Int	ITU-T G.957. Annex-K
3.14.7	Receiver Sensitivity for STM-4 Opt Int	ITU-T G.957. Annex-K

### 3.15 Interface 14 : STM-64 Optical

S.No.	Parameter Name	Standard Name
3.15.1	Input Jitter Tolerance for STM-64 Opt	ITU-T G.825. Annex-K
3.15.2	Mean Launched Power for STM-64 Opt Int	ITU-T G.691. Annex-K
3.15.3	Nominal Bit Rate with Tolerance STM-64 Opt Int	ITU-T G.707 Annex-K
3.15.4	Operating Wavelength Range for STM-64 Opt Int	ITU-T G.691. Annex-K
3.15.5	Output Jitter for STM-64 Opt Int	ITU-T G.783. Annex-K
3.15.6	Receiver Overload for STM-64 Opt Int	ITU-T G.691. Annex-K

3.15.7	Receiver Sensitivity for STM-64 Opt Int	ITU-T G.691. Annex-K
--------	---	----------------------

### 3.16 Interface 15 : WiFi

S.No.	Parameter Name	Standard Name
3.16.1	2.4 GHz WiFi Radio Conformance	ETSI EN 300 328 or FCC CFR47 pt 15.247 or FCC CFR47 pt 15.249. Annex-G3
3.16.2	5 GHz WiFi Radio Conformance	ETSI EN 301 893 or FCC CFR47 pt 15.407 or FCC CFR47 pt 15.249. Annex-G3
3.16.3	EIRP for Wifi Interface	Latest NFAP and GSRs issued by DoT WPC. Annex-G2
3.16.4	Frequency for WiFi equipments	DoT WPC GSR No. 45(E) 1048(E). Annex-G1

## 4. Variant 4 : VHF UHF Fixed Station

### 4.1 Parameters Linked with Product Variant

S.No.	Parameter Name	Standard Name
4.1.1	Conducted And Radiated Emission - Class B	TEC EMI EMC Standard CISPR 22/32 EN55022/32. Annex-B
4.1.2	Conformance to standards for VHF or UHF Radio Systems	ETSI EN 300xxx 301-xxx. Annex-C3
4.1.3	Frequency for VHF or UHF equipments	NFAP. Annex-C1
4.1.4	Immunity to AC Voltage Dips and Short Interruptions	TEC EMI EMC Standard EN/IEC:61000-4-11. Annex-B
4.1.5	Immunity to DC Voltage Dips and Short Interruptions	EN/IEC:61000-4-29. Annex-B
4.1.6	Immunity to Electrostatic Discharge	TEC EMI EMC Standard EN/IEC:61000-4-2. Annex-B
4.1.7	Immunity to Fast Transients (Burst)	TEC EMI EMC Standard EN/IEC:61000-4-4. Annex-B
4.1.8	Immunity to Radiated RF	TEC EMI EMC Standard EN/IEC:61000-4-3. Annex-B
4.1.9	Immunity to RF Field Induced Conducted Disturbance	TEC EMI EMC Standard EN/IEC:61000-4-6. Annex-B
4.1.10	Immunity to Surges	TEC EMI EMC Standard EN/IEC:61000-4-5.

		Annex-B
4.1.11	IT Equipment Safety	IS 13252-1 or IEC:60950-1 or IEC 62368-1. Annex-A1
4.1.12	Max Transmit Power for UHF or VHF Fixed Stn	As per DoT/WPC license conditions. Annex-C2

#### 4.2 Interface 1 : Bluetooth Low Energy

S.No.	Parameter Name	Standard Name
4.2.1	EIRP for BLE Interface	WPC GSR 45(E). Annex-G4 (4.2)
4.2.2	Frequency of Operation for BLE Interface	Latest NFAP. Annex-G4(4.1)
4.2.3	Spurious Emission for BLE Interface	Annex G3

#### 4.3 Interface 2 : Near Field Communication

S.No.	Parameter Name	Standard Name
4.3.1	Frequency of Operation for NFC Int	Latest NFAP. Annex-G6(6.1)
4.3.2	Spurious Emission for NFC Int	Annex- G3

#### 4.4 Interface 3 : WiFi

S.No.	Parameter Name	Standard Name
4.4.1	2.4 GHz WiFi Radio Conformance	ETSI EN 300 328 or FCC CFR47 pt 15.247 or FCC CFR47 pt 15.249. Annex-G3
4.4.2	5 GHz WiFi Radio Conformance	ETSI EN 301 893 or FCC CFR47 pt 15.407 or FCC CFR47 pt 15.249. Annex-G3
4.4.3	EIRP for Wifi Interface	Latest NFAP and GSRs issued by DoT WPC. Annex-G2
4.4.4	Frequency for WiFi equipments	DoT WPC GSR No. 45(E) 1048(E). Annex-G1

### 5. Variant 5 : VHF UHF Handheld Portable Stations

#### 5.1 Parameters Linked with Product Variant

S.No.	Parameter Name	Standard Name
5.1.1	Battery Safety	IS 16046. EN/IEC 62133. Annex-A2
5.1.2	Conducted And Radiated Emission - Class B	TEC EMI EMC Standard CISPR 22/32

		EN55022/32. Annex-B
5.1.3	Conformance to standards for VHF or UHF Radio Systems	ETSI EN 300xxx 301-xxx. Annex-C3
5.1.4	Frequency for VHF or UHF equipments	NFAP. Annex-C1
5.1.5	Immunity to Electrostatic Discharge	TEC EMI EMC Standard EN/IEC:61000-4-2. Annex-B
5.1.6	Immunity to Radiated RF	TEC EMI EMC Standard EN/IEC:61000-4-3. Annex-B
5.1.7	IT Equipment Safety	IS 13252-1 or IEC:60950-1 or IEC 62368-1. Annex-A1
5.1.8	Max Transmit Power for VHF or UHF HH Stn	As per DoT/WPC license conditions. Annex-C2

### 5.2 Interface 1 : Bluetooth Low Energy

S.No.	Parameter Name	Standard Name
5.2.1	EIRP for BLE Interface	WPC GSR 45(E). Annex-G4 (4.2)
5.2.2	Frequency of Operation for BLE Interface	Latest NFAP. Annex-G4(4.1)
5.2.3	Spurious Emission for BLE Interface	Annex G3

### 5.3 Interface 2 : Near Field Communication

S.No.	Parameter Name	Standard Name
5.3.1	Frequency of Operation for NFC Int	Latest NFAP. Annex-G6(6.1)
5.3.2	Spurious Emission for NFC Int	Annex- G3

### 5.4 Interface 3 : WiFi

S.No.	Parameter Name	Standard Name
5.4.1	2.4 GHz WiFi Radio Conformance	ETSI EN 300 328 or FCC CFR47 pt 15.247 or FCC CFR47 pt 15.249. Annex-G3
5.4.2	5 GHz WiFi Radio Conformance	ETSI EN 301 893 or FCC CFR47 pt 15.407 or FCC CFR47 pt 15.249. Annex-G3
5.4.3	EIRP for Wifi Interface	Latest NFAP and GSRs issued by DoT WPC. Annex-G2
5.4.4	Frequency for WiFi equipments	DoT WPC GSR No. 45(E) 1048(E). Annex-G1

## 6. Variant 6 : VHF UHF Mobile Stations

### 6.1 Parameters Linked with Product Variant

S.No.	Parameter Name	Standard Name
6.1.1	Battery Safety	IS 16046. EN/IEC 62133. Annex-A2
6.1.2	Conducted And Radiated Emission - Class B	TEC EMI EMC Standard CISPR 22/32 EN55022/32. Annex-B
6.1.3	Conformance to standards for VHF or UHF Radio Systems	ETSI EN 300xxx 301-xxx. Annex-C3
6.1.4	Frequency for VHF or UHF equipments	NFAP. Annex-C1
6.1.5	Immunity to AC Voltage Dips and Short Interruptions	TEC EMI EMC Standard EN/IEC:61000-4-11. Annex-B
6.1.6	Immunity to DC Voltage Dips and Short Interruptions	EN/IEC:61000-4-29. Annex-B
6.1.7	Immunity to Electrostatic Discharge	TEC EMI EMC Standard EN/IEC:61000-4-2. Annex-B
6.1.8	Immunity to Fast Transients (Burst)	TEC EMI EMC Standard EN/IEC:61000-4-4. Annex-B
6.1.9	Immunity to Radiated RF	TEC EMI EMC Standard EN/IEC:61000-4-3. Annex-B
6.1.10	Immunity to RF Field Induced Conducted Disturbance	TEC EMI EMC Standard EN/IEC:61000-4-6. Annex-B
6.1.11	Immunity to Surges	TEC EMI EMC Standard EN/IEC:61000-4-5. Annex-B
6.1.12	IT Equipment Safety	IS 13252-1 or IEC:60950-1 or IEC 62368-1. Annex-A1
6.1.13	Max Transmit Power for VHF or UHF Mob Stn	As per DoT/WPC license conditions. Annex-C2

### 6.2 Interface 1 : Bluetooth Low Energy

S.No.	Parameter Name	Standard Name
6.2.1	EIRP for BLE Interface	WPC GSR 45(E). Annex-G4 (4.2)
6.2.2	Frequency of Operation for BLE Interface	Latest NFAP. Annex-G4(4.1)

6.2.3	Spurious Emission for BLE Interface	Annex G3
-------	-------------------------------------	----------

### 6.3 Interface 2 : Near Field Communication

S.No.	Parameter Name	Standard Name
6.3.1	Frequency of Operation for NFC Int	Latest NFAP. Annex-G6(6.1)
6.3.2	Spurious Emission for NFC Int	Annex- G3

### 6.4 Interface 3 : WiFi

S.No.	Parameter Name	Standard Name
6.4.1	2.4 GHz WiFi Radio Conformance	ETSI EN 300 328 or FCC CFR47 pt 15.247 or FCC CFR47 pt 15.249. Annex-G3
6.4.2	5 GHz WiFi Radio Conformance	ETSI EN 301 893 or FCC CFR47 pt 15.407 or FCC CFR47 pt 15.249. Annex-G3
6.4.3	EIRP for Wifi Interface	Latest NFAP and GSRs issued by DoT WPC. Annex-G2
6.4.4	Frequency for WiFi equipments	DoT WPC GSR No. 45(E) 1048(E). Annex-G1